

Power Splitter/Combiner

EDK0027-B023081



2021-01-04 Rev. 0



75Ω 2 Way-0° Power Divider


5-1000MHz

Outline Drawing(mm)




Electrical structure


Fig K



Recommended layout(mm)



Electrical schematic



Pin Connections

SUM PORT	6
PORT 1	4
PORT 2	3
GROUND	1
Not connected (ground)	2,5

Features


- Operating temperature range: -40°C to +85°C
- Storage temperature range: -55°C to +100°C
- Input Power: 1W
- DC Current: 240mA

Applications


- For catv
- For broadband and wireless communications

Electrical Specifications:TA=25°C, 0dBm, Z0=75Ω

Parameter	Test Conditions	Units	Min	Typ	Max
Main line Loss (Pin6-4)	5-1000MHz	dB	—	0.5	1.2
Main line Loss (Pin6-3)	5-1000MHz	dB	—	0.5	1.2
Input Return Loss	5-1000MHz	dB	16.0	35.0	—
Output Return Loss 1	5-1000MHz	dB	16.0	25.0	—
Output Return Loss 2	5-1000MHz	dB	16.0	28.0	—
Isolation	5-1000MHz	dB	18.0	28.0	—



Carrier Tape Orientation



Tape & Reel Information

Parameter	Units	Value
Qty per reel	PCS	1500
Reel Size	mm	330
Tape Width	mm	16.00
Pitch	mm	12.00
Ao	mm	6.20
Bo	mm	8.10
Ko	mm	3.80